

General Disclaimer

One or more of the Following Statements may affect this Document

- This document has been reproduced from the best copy furnished by the organizational source. It is being released in the interest of making available as much information as possible.
- This document may contain data, which exceeds the sheet parameters. It was furnished in this condition by the organizational source and is the best copy available.
- This document may contain tone-on-tone or color graphs, charts and/or pictures, which have been reproduced in black and white.
- This document is paginated as submitted by the original source.
- Portions of this document are not fully legible due to the historical nature of some of the material. However, it is the best reproduction available from the original submission.

MCR-76-465

CONTRACT NAS8-31912

FINAL REPORT

October 1976

Analytical Study of Lightweight Acoustic Shrouds for Shuttle Experiments and Payloads

(NASA-CR-150116) ANALYTICAL STUDY OF
LIGHTWEIGHT ACOUSTIC SHROUDS FOR SHUTTLE
EXPERIMENTS AND PAYLOADS Final Report
(Martin Marietta Corp.)

N77-12113

118 p HC A06/MF A01

CSCL 22B G3/16

Unclas
56566



MARTIN MARIETTA

MCR-76-465
Contract NAS8-31912

October 1976

FINAL REPORT

ANALYTICAL STUDY
OF
LIGHTWEIGHT ACOUSTIC SHROUDS
FOR
SHUTTLE EXPERIMENTS AND PAYLOADS

Contract NAS8-31912

Prepared for:
National Aeronautics and Space Administration
George C. Marshall Space Flight Center
Huntsville, Alabama

Prepared by:
John Baratono
and
Paul Rader

Martin Marietta Corporation
Denver Division
Denver, Colorado 80201

FOREWORD

This report presents the results of a study performed for the Marshall Space Flight Center under Contract NAS8-31912. This work was a continuation of previous studies which indicated that practical, lightweight, acoustic shrouds could provide noise protection for a high percentage of the total experiment population for Space Shuttle. Specifically, this study was directed towards investigating the effects of a helium filled liner to reduce shroud weight and increase noise reduction.

CONTENTS

	<u>Page</u>
FOREWORD	ii
CONTENTS	iii
INTRODUCTION	1
TEST DESCRIPTION	2
Shroud/Test Configurations	2
Instrumentation and Data Reduction	4
DATA ANALYSIS	5
External Acoustic Levels	5
Internal Acoustic Levels	5
Noise Reduction	5
CONCLUSIONS AND RECOMMENDATIONS	7
REFERENCES	9
ABBREVIATIONS AND ACRONYMS	10
APPENDIX A: Test Data	A-1 thru A-86

ILLUSTRATIONS

<u>Figure</u>		<u>Page</u>
1	Shroud Configuration	11
2	Mylar Liner Suspended in Acoustic Chamber	12
3	Microphone Locations	13
4	Interior View of Liner Showing Internal Microphones	14
5	Comparison of External SPL's and Control Average During Shroud/Liner-Air Acoustic Test	15
6	Comparison of Average External Sound Pressure Levels Applicable to Shroud/Liner Tests	16
7	Comparison of Average Internal Sound Pressure Levels Applicable to the Four Shroud/Liner Tests	17
8	Comparison of Average Internal Sound Pressure Levels for Wire Shroud/Liner and Composite Shroud/Liner	18
9	Noise Reduction from Composite Shroud (Baseline Configuration)	19
10	Noise Reduction from Composite Shroud with Empty Liner	20
11	Noise Reduction from Composite Shroud with Liner Filled with Air	21
12	Noise Reduction from Composite Shroud with Liner Filled with Helium	22
13	Noise Reduction from Screen Enclosed Liner Filled with Air	23
14	Noise Reduction from Screen Enclosed Liner Filled with Helium	24
15	Comparison of Noise Reduction Obtained for Four Different Shroud Configurations	25
16	Comparison of Noise Reduction from Air and Helium Filled Liner	26
17	Comparison of Helium Versus Air Delta dB Noise Reduction	27
18	Comparison of Noise Reduction Data for Six Test Configurations	28

ILLUSTRATIONS (Continued)

Tables

Page

1	Shroud Weights	3
---	--------------------------	---

INTRODUCTION

This report presents a description and results of acoustic tests performed on an STS payload shroud simulator to determine the effects of a helium filled liner on the noise reduction characteristics. The basic test program included the following configurations:

1. Bare Shroud (baseline configuration);
2. Shroud with empty liner;
3. Shroud with liner filled with air; and
4. Shroud with liner filled with helium.

The results of this test series indicated negligible effects from the helium and two additional configurations were tested to provide additional information.

1. Liner filled with air; and
2. Liner filled with helium.

The data from these configurations indicated increased noise reduction from the use of helium.

TEST DESCRIPTION

Shroud/Test Configurations

Tests were conducted on two shroud configurations. The first configuration consisted of a composite fiberglass shroud and mylar liner restrained by a metal screen and ring frame stiffeners to provide support to the gas bag liner so that the gas layer could be maintained at a relatively uniform thickness of 5 cm (2 inches). A sketch of the shroud configuration is shown in Figure 1. Double walled mylar liners were also installed on the cylinder end caps (not shown in the sketch) to eliminate possible flanking paths. The shroud was approximately 0.9 meters in diameter and 1.8 meters long.

For the second configuration, the mylar liner was removed from the composite shroud and the outer surface was restrained by a wire mesh screen as shown in Figure 2.

The shroud was suspended on nylon rope within the acoustic chamber and exposed to a simulated Shuttle payload bay acoustic environment produced by two Wyle WAS 3000 noise generators coupled to the chamber at top and bottom.

Tests were conducted on the following configurations:

1. Empty shroud (baseline configuration);
2. Shroud with empty liner;
3. Shroud with liner filled with air;

4. Shroud with liner filled with helium;
5. Screen enclosed liner filled with air; and
6. Screen enclosed liner filled with helium.

A small vacuum pump was used to collapse the liner prior to filling with helium. For all configurations in which the liner was filled with either air or helium, only a sufficient gas pressure (nominally 3448 N/m^2 , or 0.5 psi) was used to expand the enclosed liner to the 5 cm wall spacing.

The weights of the shroud configurations tested are given in Table 1.

TABLE 1. SHROUD WEIGHTS

Configuration	Total Weight Including End Caps Kg (lbs)	Effective Surface Weight Kg/m^2 (lbs/sq ft)
Composite Foam Shroud	42.2 kg (93.0 lb)	4.64 kg/m^2 (0.95 lb/ft ²)
Composite Foam Shroud with Mylar Liner	45.2 kg (99.75 lb)	5.32 kg/m^2 (1.09 lb/ft ²)
Screen Enclosed Liner Only	6.1 kg (13.5 lb)	0.93 kg/m^2 (0.19 lb/ft ²)

The effective surface weights indicated in Table 1 are based on weights and surface areas relating only to the cylindrical portions of the shrouds. The composite foam/mylar liner shroud included one layer of protective mylar between the liner and screen surface. The wire screen/mylar liner shroud included two layers of protective mylar, one on each side of the liner.

Instrumentation and Data Reduction

Each test configuration was instrumented with six external and six internal microphones at locations shown in Figure 3. An interior view of the liner showing internal microphone locations is shown in Figure 4. Control of the external acoustic spectrum was accomplished by electronically averaging the output signals of the six external microphones utilizing a General Radio equalizer/analyzer system.

Similarly, the average internal acoustic spectrum was obtained for the six internal microphones. In addition to the average external and internal spectra, one-third-octave band analyses were performed for each of the individual microphones for each test configuration. These data are presented in the appendix to this report.

REPRODUCIBILITY OF THE
ORIGINAL PAGE IS POOR

DATA ANALYSIS

External Acoustic Levels

The external acoustic environment was controlled to a spectrum approximating the Shuttle payload bay environment by electronically averaging the output signals of the six external microphones. A typical plot of the levels at individual microphone locations and of the control average showing the variations in one-third-octave bands is shown in Figure 5. A comparison of electronic averages of the external level for all four tests which used the composite shroud is presented in Figure 6. These data indicate that control of the external environment was very repeatable for the different test configurations utilizing the composite shroud.

Internal Acoustic Levels

The average internal levels from the four tests of the composite shroud configurations are shown in Figure 7. Internal levels from the two screen enclosed liner tests are presented in Figure 8 and compared to the measured levels obtained from the shroud/liner filled with helium.

Noise Reduction

Noise reduction plots for the six test configurations are shown in Figures 9 through 14. In each case the noise reduction values were obtained from the difference between the average external and internal one-third-octave band levels.

A comparison of the noise reduction plots for the four tests which utilized the composite shroud is shown in Figure 15. The noise reductions obtained from the screen enclosed liner filled with air and helium are shown in Figure 16.

In addition to the individual noise reduction data presented in the preceding figures, a direct comparison of the effects of the air and helium is shown in Figure 17. The plots in Figure 17 represent the difference in noise reduction for helium versus air, for the liner in the composite shroud and in the wire screen shroud.

Figure 18 shows the noise reduction plots for the six tests performed in this study and the amount of noise reduction provided by each configuration.

CONCLUSIONS AND RECOMMENDATIONS

Conclusions

1. A comparison of helium versus air in the screen enclosed liner indicated that the helium provided an increase in noise reduction of approximately 3 dB in one-third-octave bands above 800 Hz. There was no significant change in noise reduction below 800 Hz.
2. The liner installed in the composite shroud produced an increase of 8 to 10 dB in noise reduction at frequencies above 400 Hz. However, at frequencies above the second acoustic mode of the cylinder, there was no significant difference in the noise reduction achieved with the liner empty, filled with air, or filled with helium.
3. At the first and second acoustic modes of the cylinder (approximately 100 and 200 Hz, respectively), the increased absorption provided by the gas filled liner produced an 8 to 10 dB improvement in noise reduction compared to the empty composite shroud.
4. The results of this study indicate that the use of helium in Shuttle payload shrouds would not provide a significant improvement in noise reduction compared to more conventional configurations, at least for the thickness (5 cm) of gas layer investigated. Furthermore, we believe that the problems in design and fabrication associated with containing the helium would significantly increase shroud costs compared to conventional configurations.

Recommendations

The results of this and previous studies indicate that light-weight shrouds can be developed which can reduce the payload bay acoustic environment to levels which will allow the use of components previously qualified and flown on other boosters. The cost savings associated with elimination of the requalification program and test and flight failures could be significant.

It is recommended that a full-scale prototype shroud be developed to determine the noise reduction achievable and the potential cost savings estimated from previous analyses performed under contract NAS8-31535. In addition, analyses should be conducted to assess the thermal control impact of acoustic shrouds during the various phases of the Shuttle missions. Shroud deployment design concepts should also be investigated.

REPRODUCIBILITY OF THE
ORIGINAL PAGE IS POOR

REFERENCES

1. W. P. Rader, et al, Analytical Trade Study of the STS Payload Environment, MCR-76-166, Martin Marietta Corporation, March 1976.

ABBREVIATIONS AND ACRONYMS

cm	Centimeter
dB	Decibel
ft	Feet
Hz	Hertz
in.	Inch
kg	Kilogram
lb	Pound
m	Meter
MMC	Martin Marietta Corporation
MSFC	Marshall Space Flight Center
NASA	National Aeronautics and Space Administration
N	Newton
psi	Pounds per square inch
SPL	Sound pressure level in dB re $20\mu\text{N}/\text{m}^2$
STS	Space Transportation System




Figure 1. Shroud Configuration.

REPRODUCIBILITY OF THE
ORIGINAL PAGE IS POOR




Figure 2. Mylar Liner Suspended in Acoustic Chamber.




Figure 3. Microphone Locations.




Figure 4. Interior View of Liner Showing Internal Microphones.




Figure 5. Comparison of External SPL's and Control Average During Shroud/Liner-Air Acoustic Test.




Figure 6. Comparison of Average External Sound Pressure Levels Applicable to Shroud/Liner Tests.




Figure 7. Comparison of Average Internal Sound Pressure Levels Applicable to the Four Shroud/Liner Tests.




Figure 8. Comparison of Average Internal Sound Pressure Levels for Wire Shroud/Liner and Composite Shroud/Liner.




Figure 9. Noise Reduction From Composite Shroud (Baseline Configuration).




Figure 10. Noise Reduction From Composite Shroud With Empty Liner.




Figure 11. Noise Reduction From Composite Shroud With Liner Filled With Air.




Figure 12. Noise Reduction From Composite Shroud With Liner Filled With Helium.




Figure 13. Noise Reduction From Screen Enclosed Liner Filled With Air.




Figure 14. Noise Reduction From Screen Enclosed Liner Filled With Helium.




Figure 15. Comparison of Noise Reduction Obtained For Four Different Shroud Configurations.




Figure 16. Comparison of Noise Reduction From Air and Helium Filled Liner.




Figure 17. Comparison of Helium Versus Air Delta dB Noise Reduction.




Figure 18. Comparison of Noise Reduction Data for Six Test Configurations.

A1


APPENDIX A TEST DATA

CONTENTS

<u>Plot No.</u>		<u>Page</u>
<u>Empty Composite Shroud Data</u>		
1	External Microphone Average Plot	A3
2-7	Individual External Microphone Plots	A4-A9
8	Internal Microphone Average Plot	A10
9-14	Individual Internal Microphone Plots	A11-A16
<u>Empty Liner Composite Shroud Data</u>		
15	External Microphone Average	A17
16-21	Individual External Microphone Plots	A18-A23
22	Internal Microphone Average Plot	A24
23-28	Individual Internal Microphone Plots	A25-A30
<u>0.5 psi Air, Composite Shroud Data</u>		
29	External Microphone Average Plot	A31
30-35	Individual External Microphone Plots	A32-A37
36	Internal Microphone Average Plot	A38
37-42	Individual Internal Microphone Plots	A39-A44
<u>0.5 psi He, Composite Shroud Data</u>		
43	External Microphone Average Plot	A45
44-49	Individual External Microphone Plots	A46-A51
50	Internal Microphone Average Plot	A52
51-56	Individual Internal Microphone Plots	A53-A58
<u>5 psi Air, Wire Shroud Data</u>		
57	External Microphone Average Plot	A59
58-63	Individual External Microphone Plots	A60-A65
64	Internal Microphone Average Plot	A66
65-70	Individual Internal Microphone Plots	A67-A72
<u>10 psi He, Wire Shroud Data</u>		
71	External Microphone Average Plot	A73
72-77	Individual External Microphone Plots	A74-A79
78	Internal Microphone Average Plot	A80
79-84	Individual Internal Microphone Plots	A81-A86

REPRODUCIBILITY OF THE
ORIGINAL PAGE IS POOR

ACOUSTIC DATA SHEET



TEST ITEM COMP. SHROUD

TYPE OF TEST EVAL

PROGRAM SS

DATE 9-16-76

RUN NO. 1

MICROPHONE NO. 1M-6M AUG

OVERALL LEVEL 145

RUN DURATION 10 SEC

TEST ENGINEER SNYDER


TEST TECHNICIAN REEDERSON

REMARKS EMPTY SHROUD

Plot #1

EXTERNAL MICROPHONE AVERAGE

ACOUSTIC DATA SHEET



TEST ITEM Comp. SHROUD

TYPE OF TEST EVAL

PROGRAM SS

DATE 9-16-76

RUN NO. 3

MICROPHONE NO. 1M

OVERALL LEVEL 145

RUN DURATION 10 SEC

TEST ENGINEER SNYDER


TEST TECHNICIAN ROBERTSON

REMARKS EMPTY SHROUD

Plot #2

-EXTERNAL-

ACOUSTIC DATA SHEET



TEST ITEM Comp. Jitrud

TYPE OF TEST EVAL

PROGRAM SS

DATE 9-16-76

RUN NO. 4

MICROPHONE NO. 2m

OVERALL LEVEL 175.5

RUN DURATION 10 SEC

TEST ENGINEER SNYDER

TEST TECHNICIAN ROBINSON

REMARKS EMPTY JTRUD


Plot #3

EXTERNAL

A5

REPRODUCIBILITY OF THE
ORIGINAL PAGE IS POOR

ACOUSTIC DATA SHEET



TEST ITEM COMP. SHROUD

TYPE OF TEST EVAL

PROGRAM SS

DATE 9-16-76

RUN NO. 5

MICROPHONE NO. 3M

OVERALL LEVEL 145

RUN DURATION 10 SEC

TEST ENGINEER SNYDER


TEST TECHNICIAN ROBERSON

REMARKS EMPTY SHROUD

Plot #4

EXTERNAL

ACOUSTIC DATA SHEET



TEST ITEM COMP SHROUD

TYPE OF TEST EVAL.

PROGRAM SS

DATE 9-16-76

RUN NO. 6

MICROPHONE NO. 4M

OVERALL LEVEL 145

RUN DURATION 10 SEC

TEST ENGINEER SNYDER


TEST TECHNICIAN ROGERSON

REMARKS EMPTY SHROUD

Plot #5

EXTERNAL

ACOUSTIC DATA SHEET



TEST ITEM COMP. SHROUD

TYPE OF TEST EVAL.

PROGRAM SS

DATE 9-16-76

RUN NO. 7

MICROPHONE NO. 5M

OVERALL LEVEL 144

RUN DURATION 10 SEC

TEST ENGINEER SNYDER

TEST TECHNICIAN ROBERSON

REMARKS EMPTY SHROUD


Plot #6

EXTERNAL

A8

REPRODUCIBILITY OF 1.1
ORIGINAL PAGE IS POOR

ACOUSTIC DATA SHEET



TEST ITEM COMP SHROUD

TYPE OF TEST EVAL

PROGRAM SS

DATE 9-16-76

RUN NO. 8

MICROPHONE NO. 6M

OVERALL LEVEL 144

RUN DURATION 10 SEC

TEST ENGINEER SNYDER


TEST TECHNICIAN ROBERSON

REMARKS EMPTY SHROUD

Plot #7

EXTERNAL

ACOUSTIC DATA SHEET



TEST ITEM COMP. SHROUD

TYPE OF TEST EVAL

PROGRAM SS

DATE 9-16-76

RUN NO. 2

MICROPHONE NO. 1-GAUG

OVERALL LEVEL 145 ON 1M

RUN DURATION 10 SEC

TEST ENGINEER SNYDER

TEST TECHNICIAN ROBERSON

REMARKS EMPTY SHROUD


Plot #8

INTERNAL MICROPHONE

AVERAGE

A10

ACOUSTIC DATA SHEET



TEST ITEM COMP. SHROUD

TYPE OF TEST EVAL

PROGRAM SS

DATE 9-16-76

RUN NO. 9

MICROPHONE NO. 1

OVERALL LEVEL 136

RUN DURATION 10 SEC

TEST ENGINEER SNYDER


TEST TECHNICIAN ROBERSON

REMARKS EMPTY SHROUD

Plot # 9

INTERNAL

ACOUSTIC DATA SHEET



TEST ITEM COMP. SHROUD

TYPE OF TEST EVAL

PROGRAM SS

DATE 9-16-76

RUN NO. 10

MICROPHONE NO. 2

OVERALL LEVEL 134

RUN DURATION 10 SEC

TEST ENGINEER SNYDER

TEST TECHNICIAN ROBERSON


REMARKS EMPTY SHROUD

Plot #10

INTERNAL

A12

ACOUSTIC DATA SHEET



TEST ITEM COMP SHROUD

TYPE OF TEST EVAL

PROGRAM SS

DATE 9-16-76

RUN NO. 11

MICROPHONE NO. 3

OVERALL LEVEL 132

RUN DURATION 10 SEC

TEST ENGINEER SNYDER


TEST TECHNICIAN ROBERSON

REMARKS EMPTY SHROUD

Plot # 11

INTERNAL

ACOUSTIC DATA SHEET



TEST ITEM COMP. SHROUD

TYPE OF TEST EVAL

PROGRAM SS

DATE 9-16-76

RUN NO. 12

MICROPHONE NO. 4

OVERALL LEVEL 137

RUN DURATION 10 SEC.

TEST ENGINEER SNYDER


TEST TECHNICIAN ROBERSON

REMARKS EMPTY SHROUD

Plot # 12

INTERNAL

ACOUSTIC DATA SHEET



TEST ITEM COMP. SHROUD

TYPE OF TEST EVAL

PROGRAM SS

DATE 9-16-76

RUN NO. 13

MICROPHONE NO. 5

OVERALL LEVEL 132

RUN DURATION 10 SEC

TEST ENGINEER SNIDER

TEST TECHNICIAN ROBERSON


REMARKS Empty Shroud

Plot #13

INTERNAL

115

ACOUSTIC DATA SHEET



TEST ITEM Comp. SHROUD

TYPE OF TEST EVAL

PROGRAM SS

DATE 9-16-76

RUN NO. 14

MICROPHONE NO. 6

OVERALL LEVEL 133.5

RUN DURATION 10 SEC

TEST ENGINEER SNYDER


TEST TECHNICIAN ROBERSON

REMARKS EMPTY SHROUD

Plot #14

INTERNAL

ACOUSTIC DATA SHEET



TEST ITEM Cenir. Shroud

TYPE OF TEST EVAL

PROGRAM SS

DATE 9-15-76

RUN NO. 15

MICROPHONE NO. 1M-6M AUG

OVERALL LEVEL 145 ON 1M

RUN DURATION 10 SEC

TEST ENGINEER SNYDER

TEST TECHNICIAN ROBERSON


REMARKS BAGS EVACUATED

Plot # 15

EXTERNAL MICROPHONE

AVERAGE

ACOUSTIC DATA SHEET




TEST ITEM Comp. Shroud
 TYPE OF TEST EVAL
 PROGRAM SS
 DATE 9-15-76
 RUN NO. 23
 MICROPHONE NO. 1M
 OVERALL LEVEL 145
 RUN DURATION 10 SEC
 TEST ENGINEER SNYDER
 TEST TECHNICIAN ROBERSON
 REMARKS BAGS EVACUATED
Plot #16

EXTERNAL

A18

REPRODUCIBILITY OF THE
ORIGINAL PAGE IS POOR

ACOUSTIC DATA SHEET



TEST ITEM COMP. SHROUD

TYPE OF TEST EVAL.

PROGRAM S.S.

DATE 9-15-76

RUN NO. 24

MICROPHONE NO. 2M

OVERALL LEVEL 146

RUN DURATION 10 SEC.

TEST ENGINEER SNYDER


TEST TECHNICIAN ROBERSON

REMARKS BAGS EVACUATED

Plot #17

EXTERNAL

ACOUSTIC DATA SHEET



TEST ITEM COMP. SHROUD

TYPE OF TEST EVAL.

PROGRAM SS

DATE 9-15-76

RUN NO. 25

MICROPHONE NO. 3M

OVERALL LEVEL 144

RUN DURATION 10 SEC

TEST ENGINEER SNYDER


TEST TECHNICIAN ROBERSON

REMARKS BAGS EVACUATED

Plot # 18

EXTERNAL

ACOUSTIC DATA SHEET



TEST ITEM COMP SHREDD

TYPE OF TEST EVAL.

PROGRAM SS

DATE 9-15-76

RUN NO. 26

MICROPHONE NO. 4M

OVERALL LEVEL 145

RUN DURATION 10 SEC.

TEST ENGINEER JAYDER

TEST TECHNICIAN ROBERSON


REMARKS BAGS EVACUATED

Plot #19

EXTERNAL

A21

ACOUSTIC DATA SHEET



TEST ITEM COMP. SHROUD

TYPE OF TEST EVAL.

PROGRAM SS

DATE 9-15-76

RUN NO. 27

MICROPHONE NO. 5M

OVERALL LEVEL 144

RUN DURATION 10SEC

TEST ENGINEER SNYDER

TEST TECHNICIAN ROBERSON

REMARKS BAGS EVACUATED


Plot # 20

EXTERNAL

A22

REPRODUCIBILITY OF THE
ORIGINAL PAGE IS POOR

ACOUSTIC DATA SHEET



TEST ITEM COMP. SHROUD

TYPE OF TEST EVAL.

PROGRAM SS

DATE 9-15-76

RUN NO. 28

MICROPHONE NO. 6M

OVERALL LEVEL 144

RUN DURATION 10 SEC

TEST ENGINEER SNYDER

TEST TECHNICIAN ROBERTSON


REMARKS BAGS EVALUATED

Plot # 21

EXTERNAL

A23

ACOUSTIC DATA SHEET



TEST ITEM COMP. SHROUD

TYPE OF TEST EVAL

PROGRAM SS

DATE 9-15-76

RUN NO. 16

MICROPHONE NO. 1-6 AUG.

OVERALL LEVEL 145 ON 1M

RUN DURATION 10 SEC

TEST ENGINEER SNYDER

TEST TECHNICIAN ROBERSON


REMARKS BAGS EVALUATED

Plot # 22

INTERNAL MICROPHONE

AVERAGE

ACOUSTIC DATA SHEET



TEST ITEM Comp. Shred

TYPE OF TEST EVAL

PROGRAM SS

DATE 9-15-76

RUN NO. 17

MICROPHONE NO. 1

OVERALL LEVEL 131

RUN DURATION 10 SEC

TEST ENGINEER SNYDER

TEST TECHNICIAN ROBERSON


REMARKS BAGS EVACUATED

Plot No. 23

INTERNAL

A25

ACOUSTIC DATA SHEET



TEST ITEM Comp. Shroud

TYPE OF TEST EVAL

PROGRAM SS

DATE 9-15-76

RUN NO. 18

MICROPHONE NO. 2

OVERALL LEVEL 130

RUN DURATION 10 SEC

TEST ENGINEER SNYDER


TEST TECHNICIAN ROBERSON

REMARKS BAGS EVACUATED

Plot # 24

INTERNAL

ACOUSTIC DATA SHEET



TEST ITEM COMP. SHROUD

TYPE OF TEST EVAL.

PROGRAM SS

DATE 9-15-76

RUN NO. 19

MICROPHONE NO. 3

OVERALL LEVEL 128

RUN DURATION 10 SEC

TEST ENGINEER SNYDER


TEST TECHNICIAN ROBERSON

REMARKS BAGS EVALUATED

Plot # 25

INTERNAL

ACOUSTIC DATA SHEET



TEST ITEM Comp. Shroud

TYPE OF TEST EVAL

PROGRAM SS

DATE 9-15-76

RUN NO 20

MICROPHONE NO. 4

OVERALL LEVEL 132

RUN DURATION 10 SEC

TEST ENGINEER SNYDER


TEST TECHNICIAN ROBERSON

REMARKS BAGS EVACUATED

Pilot #16

INTERNAL

ACOUSTIC DATA SHEET



TEST ITEM Comp. SHROUD

TYPE OF TEST EVAL

PROGRAM SS

DATE 9-15-76

RUN NO. 21

MICROPHONE NO. 5

OVERALL LEVEL 128

RUN DURATION 10 SEC

TEST ENGINEER SNYDER


TEST TECHNICIAN ROBERSON

REMARKS BAGS EVALUATED

Plot # 27

INTERNAL

ACOUSTIC DATA SHEET



TEST ITEM COMP. SHROUD

TYPE OF TEST EVAL

PROGRAM 55

DATE 9-15-76

RUN NO. 22

MICROPHONE NO. 6

OVERALL LEVEL 130

RUN DURATION 10 SEC

TEST ENGINEER SNYDER

TEST TECHNICIAN ROBERSON

REMARKS BAGS EVACUATED


Plot # 28

INTERNAL

A30

REPRODUCIBILITY OF THE
ORIGINAL PAGE IS POOR

ACOUSTIC DATA SHEET



TEST ITEM COMP SHROUD

TYPE OF TEST ENV.

PROGRAM SE

DATE 9-15-76

RUN NO. 1

MICROPHONE NO. 1M-6A-AUG

OVERALL LEVEL 145 ON #1M

RUN DURATION 10 SEC

TEST ENGINEER SHADER

TEST TECHNICIAN ROBERSON

REMARKS AIR IN JACKET
3448. N/m²
AT (0.5 PSI)


Plot # 29

EXTERNAL MICROPHONE

AVERAGE

A31

ACOUSTIC DATA SHEET



TEST ITEM COMP. SHROUD

TYPE OF TEST EVAL.

PROGRAM SS

DATE 9-15-76

RUN NO. 3

MICROPHONE NO. 1M

OVERALL LEVEL 145

RUN DURATION 10 SEC

TEST ENGINEER SNYDER

TEST TECHNICIAN ROBERSON


REMARKS AIR IN JACKET

3448 N/M2
AT ~ (0.5 PSI)

Plot # 30

EXTERNAL

ACOUSTIC DATA SHEET



TEST ITEM Comp. SHROUD

TYPE OF TEST EVAL

PROGRAM SS

DATE 7-15-76

RUN NO. 4

MICROPHONE NO. 2M (145)

OVERALL LEVEL 145 CN ± 1M

RUN DURATION 10 SEC

TEST ENGINEER SNYDER

TEST TECHNICIAN ROBERSON


REMARKS 3448 N/M²
(0.5 PSI) AIR

Plot # 31

EXTERNAL

A33

ACOUSTIC DATA SHEET



TEST ITEM Comp. Shroud

TYPE OF TEST EVAL

PROGRAM SS

DATE 9-15-76

RUN NO. 5

MICROPHONE NO. 3M

OVERALL LEVEL 144

RUN DURATION 10 SEC

TEST ENGINEER SNYDER

TEST TECHNICIAN ROBERSON


REMARKS 3448. N/m²
~(0.5 PSI) AIR

Plot # 32

EXTERNAL

A34

ACOUSTIC DATA SHEET



TEST ITEM COMP. SHROUD

TYPE OF TEST EVAL

PROGRAM SS

DATE 9-15-76

RUN NO. 6

MICROPHONE NO. 4M

OVERALL LEVEL 145.5

RUN DURATION 10 SEC

TEST ENGINEER SNYDER


TEST TECHNICIAN ROBERSON

REMARKS 3448 N/M²
(0.5 PSI) AIR

Plot # 33

EXTERNAL

ACOUSTIC DATA SHEET



TEST ITEM Comp. Shroud

TYPE OF TEST EVAL

PROGRAM SS

DATE 9-15-76

RUN NO. 7

MICROPHONE NO. 5M

OVERALL LEVEL 144

RUN DURATION 10 SEC

TEST ENGINEER SNYDER

TEST TECHNICIAN ROBERTSON


REMARKS 3448 N/M²
(0.5 PSI) AIR

Plot # 34

EXTERNAL

A36

ACOUSTIC DATA SHEET



TEST ITEM COMP. SHROUD

TYPE OF TEST FLAL

PROGRAM SS

DATE 7-15-76

RUN NO. 8

MICROPHONE NO. 6M

OVERALL LEVEL 144

RUN DURATION 10 SEC

TEST ENGINEER SNYDER

TEST TECHNICIAN ROBERSON


REMARKS 3448 N/M²
(0.5 PSI) AIR

Plot No. 35

EXTERNAL

A37

ACOUSTIC DATA SHEET



TEST ITEM COMP. SHROUD

TYPE OF TEST EVAL

PROGRAM SS

DATE 9-15-76

RUN NO. 2

MICROPHONE NO. 1-6 AUG

OVERALL LEVEL 145 ON 1M

RUN DURATION 10 SEC

TEST ENGINEER 3N4DER

TEST TECHNICIAN KOBERSON

REMARKS AIR IN JACKET

3448 N/M²
AT 10.5 PSI

Plot # 36


INTERNAL MICROPHONE

AVERAGE

A38

REPRODUCIBILITY OF THE
ORIGINAL PAGE IS POOR

ACOUSTIC DATA SHEET



TEST ITEM COMP. SHROUD

TYPE OF TEST EVAL

PROGRAM SS

DATE 9-15-76

RUN NO. 9

MICROPHONE NO. 1

OVERALL LEVEL 127

RUN DURATION 10 SEC

TEST ENGINEER SNYDER

TEST TECHNICIAN ROBINSON


REMARKS 3448 N/M²
(C. 5 PSI) AIR

Plot # 37

INTERNAL

A39

ACOUSTIC DATA SHEET



TEST ITEM COMP. SHROUD

TYPE OF TEST EVAL

PROGRAM SS

DATE 9-15-76

RUN NO. 10

MICROPHONE NO. 2

OVERALL LEVEL 126.5

RUN DURATION 10 SEC

TEST ENGINEER SNYDER

TEST TECHNICIAN ROBERSON


REMARKS 3448. N/M²
(0.5 PSI) AIR

Plot # 38

INTERNAL

AAO

ACOUSTIC DATA SHEET



TEST ITEM COMP. SHROUD

TYPE OF TEST EVAL

PROGRAM SS

DATE 9-15-76

RUN NO. 11

MICROPHONE NO. 3

OVERALL LEVEL 125

RUN DURATION 10 SEC

TEST ENGINEER SNYDER

TEST TECHNICIAN ROBERSON


REMARKS 3448 N/AZ
C.S. PSI) AIR

Plot # 39

INTERNAL

A4.1

ACOUSTIC DATA SHEET



TEST ITEM Comp. Shroud

TYPE OF TEST EVAL

PROGRAM SS

DATE 9-15-76

RUN NO. 12

MICROPHONE NO. 4

OVERALL LEVEL 128

RUN DURATION 10 SEC

TEST ENGINEER SNYDER

TEST TECHNICIAN ROBERSON


REMARKS 3448. N/AIR

(0.5 PSI) AIR

Plot #40

INTERNAL

ACOUSTIC DATA SHEET



TEST ITEM Comp. Shield

TYPE OF TEST EVAL

PROGRAM SS

DATE 9-15-76

RUN NO. 13

MICROPHONE NO. 5

OVERALL LEVEL 124

RUN DURATION 10 SEC

TEST ENGINEER SNYDER

TEST TECHNICIAN ROBERSON

REMARKS 3448 N/M²
~(0.5 PSI) AIR


Plot # 41

INTERNAL

A43

REPRODUCIBILITY OF THE
ORIGINAL PAGE IS POOR

ACOUSTIC DATA SHEET



TEST ITEM COMP. SHROUD

TYPE OF TEST EVAL

PROGRAM SS

DATE 9-15-76

RUN NO. 14

MICROPHONE NO. 6

OVERALL LEVEL 126

RUN DURATION 10 SEC

TEST ENGINEER SNYDER


TEST TECHNICIAN ROBERSON

REMARKS 3448 N/M²
~(0.5 PSI) AIR

Plot # 42

INTERNAL

ACOUSTIC DATA SHEET



TEST ITEM COMP SHROUD

TYPE OF TEST EVAL.

PROGRAM SS

DATE 9-15-76

RUN NO. 29

MICROPHONE NO. 1M-6MA6

OVERALL LEVEL 145 CN 1M

RUN DURATION 10 SEC

TEST ENGINEER SNYDER

TEST TECHNICIAN ROBERSON


REMARKS 3448 12/1/72
HELIUM (0.5PSI)

Plot # 43

EXTERNAL MICROPHONE

AVERAGE

ACOUSTIC DATA SHEET



TEST ITEM COMP. SHROUD

TYPE OF TEST EVAL

PROGRAM SS

DATE 9-15-76

RUN NO. 37

MICROPHONE NO. 1M

OVERALL LEVEL 145

RUN DURATION 10 SEC

TEST ENGINEER SNYDER


TEST TECHNICIAN ROBERSON

REMARKS 3448 N/M²
(C. 5 PSI) HELIUM

Plot # 44

EXTERNAL

ACOUSTIC DATA SHEET



TEST ITEM COMP. SHROUD

TYPE OF TEST FLAC

PROGRAM SS

DATE 7-15-76

RUN NO. 38

MICROPHONE NO. 2M

OVERALL LEVEL 146

RUN DURATION 10 SEC

TEST ENGINEER SNYDER

TEST TECHNICIAN BERGSON

REMARKS 3448 N/A²


(C.5 PSI) HELIUM

Plot # 45

EXTERNAL

A47

ACOUSTIC DATA SHEET



TEST ITEM Comp. Shroud

TYPE OF TEST EVAL.

PROGRAM SS

DATE 9-15-76

RUN NO. 39

MICROPHONE NO. 3M

OVERALL LEVEL 145

RUN DURATION 10 SEC

TEST ENGINEER SNYDER


TEST TECHNICIAN ROBERSON

REMARKS 3448 N/A²
(0.5 PSI) HELIUM

Plot #46

EXTERNAL

ACOUSTIC DATA SHEET



TEST ITEM COMP. SHIELD

TYPE OF TEST EVAL.

PROGRAM SS

DATE 9-15-76

RUN NO. 40

MICROPHONE NO. 4M

OVERALL LEVEL 145.5

RUN DURATION 10 SEC

TEST ENGINEER SNYDER


TEST TECHNICIAN ROBERSON

REMARKS 3448N/M²
(C.5 PSI) HELIUM

Plot #47

EXTERNAL

ACOUSTIC DATA SHEET



TEST ITEM Comp. Shroud

TYPE OF TEST EVAL

PROGRAM SS

DATE 9-15-76

RUN NO. 41

MICROPHONE NO. SM

OVERALL LEVEL _____

RUN DURATION 10SEC

TEST ENGINEER SNYDER

TEST TECHNICIAN ROBERSON

(3448 NIM²)

REMARKS 0.5 PSI HELIUM


Plot # 48

EXTERNAL

A50

REPRODUCIBILITY OF THE
ORIGINAL PAGE IS POOR

ACOUSTIC DATA SHEET



TEST ITEM COMP. SHROUD

TYPE OF TEST EVAL

PROGRAM SS

DATE 9-15-76

RUN NO. 42

MICROPHONE NO. 6M

OVERALL LEVEL 144

RUN DURATION 10 SEC

TEST ENGINEER SNYDER

TEST TECHNICIAN ROBERSON


REMARKS 3448 N/m²
(0.5 PSI) (HELIUM)

Plot # 49

EXTERNAL

AS1

ACOUSTIC DATA SHEET



TEST ITEM Comp. Shroud

TYPE OF TEST EVAL

PROGRAM SS

DATE 9-15-76

RUN NO. 30

MICROPHONE NO. 1-6 AUG

OVERALL LEVEL 145 ON 1M

RUN DURATION 10 SEC

TEST ENGINEER SNYDER

TEST TECHNICIAN ROBERSON

REMARKS 3448 N/m²
(0.5 PSI) HELIUM


Plot # 50

INTERNAL MICROPHONE

AVERAGE

AS2

ACOUSTIC DATA SHEET



TEST ITEM COMP. SHROUD

TYPE OF TEST EVAL

PROGRAM SS

DATE 9-15-76

RUN NO. 31

MICROPHONE NO. 1

OVERALL LEVEL 127

RUN DURATION 10 SEC

TEST ENGINEER SNYDER


TEST TECHNICIAN ROBERSON

REMARKS 3448. NIM²
(0.5 PSI) HELIUM

Plot # 51

INTERNAL

ACOUSTIC DATA SHEET



TEST ITEM COMP. SHROUD

TYPE OF TEST EVAL

PROGRAM SS

DATE 9-15-76

RUN NO. 32

MICROPHONE NO. 2

OVERALL LEVEL 126

RUN DURATION 10 SEC

TEST ENGINEER SNYDER

TEST TECHNICIAN ROBERSON


REMARKS 3448. N/M²
(0.5 PSI) HELIUM

Plot # 52

INTERNAL

AS4

ACOUSTIC DATA SHEET



TEST ITEM COMP. SHROUD

TYPE OF TEST EVAL

PROGRAM SS

DATE 7-15-76

RUN NO. 33

MICROPHONE NO. 3

OVERALL LEVEL 124

RUN DURATION 10 SEC

TEST ENGINEER SNYDER

TEST TECHNICIAN ROBERSON


REMARKS 3448. NIM²
(C-5 PSI) HELIUM

Plot # 53

INTERNAL

A55

ACOUSTIC DATA SHEET



TEST ITEM Comp. Shroud

TYPE OF TEST EVAL

PROGRAM SS

DATE 9-15-76

RUN NO. 34

MICROPHONE NO. 4

OVERALL LEVEL 127.5

RUN DURATION 10 SEC

TEST ENGINEER SNYDER

TEST TECHNICIAN ROBERTSON

 $3448. \text{ N/m}^2$

REMARKS (0.5 PSI) Helium

Plot # 54

INTERNAL

1. *Journal of the American Medical Association*, 1997; 277: 1001-1005.


1998, 1999, 2000, 2001, 2002, 2003, 2004, 2005, 2006, 2007, 2008, 2009, 2010, 2011, 2012, 2013, 2014, 2015, 2016, 2017, 2018, 2019, 2020, 2021, 2022, 2023, 2024, 2025, 2026, 2027, 2028, 2029, 2030, 2031, 2032, 2033, 2034, 2035, 2036, 2037, 2038, 2039, 2040, 2041, 2042, 2043, 2044, 2045, 2046, 2047, 2048, 2049, 2050, 2051, 2052, 2053, 2054, 2055, 2056, 2057, 2058, 2059, 2060, 2061, 2062, 2063, 2064, 2065, 2066, 2067, 2068, 2069, 2070, 2071, 2072, 2073, 2074, 2075, 2076, 2077, 2078, 2079, 2080, 2081, 2082, 2083, 2084, 2085, 2086, 2087, 2088, 2089, 2090, 2091, 2092, 2093, 2094, 2095, 2096, 2097, 2098, 2099, 2100, 2101, 2102, 2103, 2104, 2105, 2106, 2107, 2108, 2109, 2110, 2111, 2112, 2113, 2114, 2115, 2116, 2117, 2118, 2119, 2120, 2121, 2122, 2123, 2124, 2125, 2126, 2127, 2128, 2129, 2130, 2131, 2132, 2133, 2134, 2135, 2136, 2137, 2138, 2139, 2140, 2141, 2142, 2143, 2144, 2145, 2146, 2147, 2148, 2149, 2150, 2151, 2152, 2153, 2154, 2155, 2156, 2157, 2158, 2159, 2160, 2161, 2162, 2163, 2164, 2165, 2166, 2167, 2168, 2169, 2170, 2171, 2172, 2173, 2174, 2175, 2176, 2177, 2178, 2179, 2180, 2181, 2182, 2183, 2184, 2185, 2186, 2187, 2188, 2189, 2190, 2191, 2192, 2193, 2194, 2195, 2196, 2197, 2198, 2199, 2200, 2201, 2202, 2203, 2204, 2205, 2206, 2207, 2208, 2209, 2210, 2211, 2212, 2213, 2214, 2215, 2216, 2217, 2218, 2219, 2220, 2221, 2222, 2223, 2224, 2225, 2226, 2227, 2228, 2229, 2230, 2231, 2232, 2233, 2234, 2235, 2236, 2237, 2238, 2239, 2240, 2241, 2242, 2243, 2244, 2245, 2246, 2247, 2248, 2249, 2250, 2251, 2252, 2253, 2254, 2255, 2256, 2257, 2258, 2259, 2260, 2261, 2262, 2263, 2264, 2265, 2266, 2267, 2268, 2269, 2270, 2271, 2272, 2273, 2274, 2275, 2276, 2277, 2278, 2279, 2280, 2281, 2282, 2283, 2284, 2285, 2286, 2287, 2288, 2289, 2290, 2291, 2292, 2293, 2294, 2295, 2296, 2297, 2298, 2299, 2300, 2301, 2302, 2303, 2304, 2305, 2306, 2307, 2308, 2309, 2310, 2311, 2312, 2313, 2314, 2315, 2316, 2317, 2318, 2319, 2320, 2321, 2322, 2323, 2324, 2325, 2326, 2327, 2328, 2329, 2330, 2331, 2332, 2333, 2334, 2335, 2336, 2337, 2338, 2339, 2340, 2341, 2342, 2343, 2344, 2345, 2346, 2347, 2348, 2349, 2350, 2351, 2352, 2353, 2354, 2355, 2356, 2357, 2358, 2359, 2360, 2361, 2362, 2363, 2364, 2365, 2366, 2367, 2368, 2369, 2370, 2371, 2372, 2373, 2374, 2375, 2376, 2377, 2378, 2379, 2380, 2381, 2382, 2383, 2384, 2385, 2386, 2387, 2388, 2389, 2390, 2391, 2392, 2393, 2394, 2395, 2396, 2397, 2398, 2399, 2400, 2401, 2402, 2403, 2404, 2405, 2406, 2407, 2408, 2409, 2410, 2411, 2412, 2413, 2414, 2415, 2416, 2417, 2418, 2419, 2420, 2421, 2422, 2423, 2424, 2425, 2426, 2427, 2428, 2429, 2430, 2431, 2432, 2433, 2434, 2435, 2436, 2437, 2438, 2439, 2440, 2441, 2442, 2443, 2444, 2445, 2446, 2447, 2448, 2449, 2450, 2451, 2452, 2453, 2454, 2455, 2456, 2457, 2458, 2459, 2460, 2461, 2462, 2463, 2464, 2465, 2466, 2467, 2468, 2469, 2470, 2471, 2472, 2473, 2474, 2475, 2476, 2477, 2478, 2479, 2480, 2481, 2482, 2483, 2484, 2485, 2486, 2487, 2488, 2489, 2490, 2491, 2492, 2493, 2494, 2495, 2496, 2497, 2498, 2499, 2500, 2501, 2502, 2503, 2504, 2505, 2506, 2507, 2508, 2509, 2510, 2511, 2512, 2513, 2514, 2515, 2516, 2517, 2518, 2519, 2520, 2521, 2522, 2523, 2524, 2525, 2526, 2527, 2528, 2529, 2530, 2531, 2532, 2533, 2534, 2535, 2536, 2537, 2538, 2539, 2540, 2541, 2542, 2543, 2544, 2545, 2546, 2547, 2548, 2549, 2550, 2551, 2552, 2553, 2554, 2555, 2556, 2557, 2558, 2559, 2560, 2561, 2562, 2563, 2564, 2565, 2566, 2567, 2568, 2569, 2570, 2571, 2572, 2573, 2574, 2575, 2576, 2577, 2578, 2579, 2580, 2581, 2582, 2583, 2584, 2585, 2586, 2587, 2588, 2589, 2590, 2591, 2592, 2593, 2594, 2595, 2596, 2597, 2598, 2599, 2600, 2601, 2602, 2603, 2604, 2605, 2606, 2607, 2608, 2609, 2610, 2611, 2612, 2613, 2614, 2615, 2616, 2617, 2618, 2619, 2620, 2621, 2622, 2623, 2624, 2625, 2626, 2627, 2628, 2629, 2630, 2631, 2632, 2633, 2634, 2635, 2636, 2637, 2638, 2639, 2640, 2641, 2642, 2643, 2644, 2645, 2646, 2647, 2648, 2649, 2650, 2651, 2652, 2653, 2654, 2655, 2656, 2657, 2658, 2659, 2660, 2661, 2662, 2663, 2664, 2665, 2666, 2667, 2668, 2669, 2670, 2671, 2672, 2673, 2674, 2675, 2676, 2677, 2678, 2679, 26

100

A56

REPRODUCIBILITY OF THE
ORIGINAL PAGE IS POOR

ACOUSTIC DATA SHEET



TEST ITEM COMP. SHIELD

TYPE OF TEST EVAL

PROGRAM SS

DATE 9-15-76

RUN NO. 35

MICROPHONE NO. 5

OVERALL LEVEL 124.5

RUN DURATION 10 SEC

TEST ENGINEER SNYDER

TEST TECHNICIAN ROBERSON


REMARKS 3448 N/M²
(C.5 PSI) HELIUM

Plot # 55

INTERNAL

A57

ACOUSTIC DATA SHEET



TEST ITEM Comp. Shroud

TYPE OF TEST EVAL.

PROGRAM SS

DATE 9-15-76

RUN NO. 36

MICROPHONE NO. 6

OVERALL LEVEL _____

RUN DURATION 10 SEC

TEST ENGINEER SNYDER

TEST TECHNICIAN ROBERSON


REMARKS 3448. N/m²
(0.5 PSI) HELIUM

Plot #56

INTERNAL

A58

ACOUSTIC DATA SHEET



TEST ITEM Comp. Shroud
Liner

TYPE OF TEST EVAL

PROGRAM SS

DATE 9-17-76

RUN NO. 1

MICROPHONE NO. 1M-6M AUG

OVERALL LEVEL 145 ON 1M

RUN DURATION 10 SEC

TEST ENGINEER SNYDER

TEST TECHNICIAN ROBERTSON

REMARKS BAGS WITH AIR


Plot # 57

EXTERNAL MICROPHONE

AVERAGE

A59

ACOUSTIC DATA SHEET



TEST ITEM LINER

TYPE OF TEST EVAL

PROGRAM SS

DATE 9-17-76

RUN NO. 9

MICROPHONE NO. 1M

OVERALL LEVEL 145

RUN DURATION 10 SEC

TEST ENGINEER SNYDER

TEST TECHNICIAN ROBERSON


REMARKS AIR IN LINER

Plot #58

EXTERNAL

A60

ACOUSTIC DATA SHEET



TEST ITEM LINER

TYPE OF TEST EVAL

PROGRAM SS

DATE 9-17-76

RUN NO. 10

MICROPHONE NO. 2M

OVERALL LEVEL 146.5

RUN DURATION 10SEC

TEST ENGINEER SNYDER


TEST TECHNICIAN ROBERSON

REMARKS AIR IN LINER

Plot # 59

EXTERNAL

ACOUSTIC DATA SHEET



TEST ITEM LINER

TYPE OF TEST EVAL

PROGRAM SS

DATE 9-17-76

RUN NO. 11

MICROPHONE NO. 3M

OVERALL LEVEL 145

RUN DURATION 10 SEC

TEST ENGINEER SNYDER


TEST TECHNICIAN ROBERSON

REMARKS AIR IN LINER

Plot #60

EXTERNAL

ACOUSTIC DATA SHEET



TEST ITEM LINER

TYPE OF TEST EVAL.

PROGRAM SS

DATE 9-17-76

RUN NO. 12

MICROPHONE NO. 4M

OVERALL LEVEL 145

RUN DURATION 10 SEC

TEST ENGINEER SNYDER


TEST TECHNICIAN ROBERSON

REMARKS AIR IN LINER

Plot # 61

EXTERNAL

ACOUSTIC DATA SHEET



TEST ITEM LINER

TYPE OF TEST EVAL

PROGRAM SS

DATE 9-17-76

RUN NO. 13

MICROPHONE NO. 5M

OVERALL LEVEL 143.5

RUN DURATION 10 SEC

TEST ENGINEER SNYDER


TEST TECHNICIAN ROBERSON

REMARKS AIR IN LINER

Plot # 62

EXTERNAL

ACOUSTIC DATA SHEET



TEST ITEM LINER

TYPE OF TEST ENV

PROGRAM SS

DATE 4-17-76

RUN NO. 14

MICROPHONE NO. 6M

OVERALL LEVEL 144

RUN DURATION 10 SEC

TEST ENGINEER SNYDER


TEST TECHNICIAN RODERSEN

REMARKS AIR IN LINER

Plot #63

EXTERNAL

ACOUSTIC DATA SHEET



TEST ITEM LINER

TYPE OF TEST EVAL

PROGRAM SE

DATE 9-17-76

RUN NO. 2

MICROPHONE NO. 1-6 AUG

OVERALL LEVEL 1450N1M

RUN DURATION 10 SEC

TEST ENGINEER SNYDER

TEST TECHNICIAN ROBERSON

REMARKS AIR IN LINER

Plot # 64


INTERNAL MICROPHONE

AVERAGE

A66

REPRODUCIBILITY OF THE
ORIGINAL PAGE IS POOR

ACOUSTIC DATA SHEET



TEST ITEM LINER

TYPE OF TEST EVAL

PROGRAM SS

DATE 9-17-76

RUN NO. 3

MICROPHONE NO. 1

OVERALL LEVEL 139

RUN DURATION 10 SEC

TEST ENGINEER SNYDER


TEST TECHNICIAN ROBERSON

REMARKS AIR IN - WER

Plot #65

INTERNAL

ACOUSTIC DATA SHEET



TEST ITEM LINER

TYPE OF TEST EVAL

PROGRAM SS

DATE 9-17-76

RUN NO. 4

MICROPHONE NO. 2

OVERALL LEVEL 138

RUN DURATION 10 SEC

TEST ENGINEER SNYDER


TEST TECHNICIAN ROBERSON

REMARKS AIR IN LINER

Plot #66

INTERNAL

ACOUSTIC DATA SHEET



TEST ITEM LINEAR

TYPE OF TEST EVAL

PROGRAM SS

DATE 9-17-76

RUN NO. 5

MICROPHONE NO. 3

OVERALL LEVEL 137.5

RUN DURATION 10 SEC.

TEST ENGINEER SNYDER


TEST TECHNICIAN ROBINSON

REMARKS AIR IN LINE

Plot # 67

INTERNAL

ACOUSTIC DATA SHEET



TEST ITEM LINER

TYPE OF TEST EVAL

PROGRAM SS

DATE 9-17-76

RUN NO. 6

MICROPHONE NO. 4

OVERALL LEVEL 138

RUN DURATION 10 SEC

TEST ENGINEER SNYDER

TEST TECHNICIAN ROBERSON

REMARKS AIR IN LINER


Plot # 68

INTERNAL

A70

REPRODUCIBILITY OF THE
ORIGINAL PAGE IS POOR

ACOUSTIC DATA SHEET



TEST ITEM LINER

TYPE OF TEST Env

PROGRAM SS

DATE 9-17-76

RUN NO. 7

MICROPHONE NO. 5

OVERALL LEVEL 140

RUN DURATION 10 SEC

TEST ENGINEER SNYDER

TEST TECHNICIAN GREENSON


REMARKS AIR IN LINER

Plot # 69

INTERNAL

A71

ACOUSTIC DATA SHEET



TEST ITEM LINER

TYPE OF TEST EVAL

PROGRAM SS

DATE 9-17-76

RUN NO. 8

MICROPHONE NO. 6

OVERALL LEVEL 136.5

RUN DURATION 10 SEC

TEST ENGINEER SNYDER


TEST TECHNICIAN ROBERSON

REMARKS AIR IN LINER

Plot #70

INTERNAL

ACOUSTIC DATA SHEET



TEST ITEM LINER

TYPE OF TEST EVAL

PROGRAM SS

DATE 9-17-76

RUN NO. 15

MICROPHONE NO. IM-6A AUG

OVERALL LEVEL 145 ON IM

RUN DURATION 10 SEC

TEST ENGINEER SNYDER

TEST TECHNICIAN ROBERSON


REMARKS HELIUM IN LINER

Plot # 71

EXTERNAL MICROPHONE

AVERAGE

ACOUSTIC DATA SHEET



TEST ITEM LINER

TYPE OF TEST EVAL.

PROGRAM SS

DATE 9-17-76

RUN NO. 23

MICROPHONE NO. 1M

OVERALL LEVEL 145

RUN DURATION 10 SEC

TEST ENGINEER SNYDER


TEST TECHNICIAN ROBERSON

REMARKS HELIUM

Plot #72

EXTERNAL

ACOUSTIC DATA SHEET



TEST ITEM LINER

TYPE OF TEST EVAL

PROGRAM 35

DATE 9-17-76

RUN NO. 29

MICROPHONE NO. 2W

OVERALL LEVEL 146.5

RUN DURATION 10 SEC

TEST ENGINEER SNYDER


TEST TECHNICIAN ROBERTSON

REMARKS HELIUM

Plot # 73

EXTERNAL

ACOUSTIC DATA SHEET



TEST ITEM LINER

TYPE OF TEST EVAL

PROGRAM ES

DATE 9-17-76

RUN NO. 25

MICROPHONE NO. 3M

OVERALL LEVEL 145

RUN DURATION 10 SEC.

TEST ENGINEER SNYDER

TEST TECHNICIAN ROBERSON

REMARKS HELIUM


Plot # 74

EXTERNAL

A76

REPRODUCIBILITY OF THE
ORIGINAL PAGE IS POOR

ACOUSTIC DATA SHEET



TEST ITEM LINER

TYPE OF TEST EVAL

PROGRAM SS

DATE 4-17-76

RUN NO. 26

MICROPHONE NO. 4M

OVERALL LEVEL _____

RUN DURATION 10 SEC

TEST ENGINEER SNYDER

TEST TECHNICIAN ROBERTSON


REMARKS HELIUM

Plot # 75

EXTERNAL

A77

ACOUSTIC DATA SHEET



TEST ITEM LINER

TYPE OF TEST EVAL

PROGRAM SS

DATE 9-17-76

RUN NO. 27

MICROPHONE NO. 5M

OVERALL LEVEL 144

RUN DURATION 10 SEC

TEST ENGINEER SNYDER


TEST TECHNICIAN ROBERSON

REMARKS HELIUM

Plot # 76

EXTERNAL

ACOUSTIC DATA SHEET



TEST ITEM LINER

TYPE OF TEST EVAL

PROGRAM SS

DATE 9-17-76

RUN NO. 28

MICROPHONE NO. 6M

OVERALL LEVEL _____

RUN DURATION 10 SEC

TEST ENGINEER SIN Y DER


TEST TECHNICIAN ROBERSON

REMARKS HELIUM

Plot # 77

EXTERNAL

ACOUSTIC DATA SHEET



TEST ITEM LINER

TYPE OF TEST EVAL

PROGRAM SS

DATE 9-17-76

RUN NO. 16

MICROPHONE NO. 1-6 AVG

OVERALL LEVEL 145 on 1m

RUN DURATION 10 SEC

TEST ENGINEER SNYDER

TEST TECHNICIAN ROBERSON

REMARKS HELIUM

Plot # 78


INTERNAL MICROPHONE

AVERAGE

A80

REPRODUCIBILITY OF THE
ORIGINAL PAGE IS POOR

ACOUSTIC DATA SHEET



TEST ITEM LINER

TYPE OF TEST Equal

PROGRAM SS

DATE 7-17-76

RUN NO. 17

MICROPHONE NO. 1

OVERALL LEVEL 138

RUN DURATION 10 SEC

TEST ENGINEER SNYDER


TEST TECHNICIAN ROBERSON

REMARKS Helium

Plot # 79

INTERNAL

ACOUSTIC DATA SHEET



TEST ITEM LINER

TYPE OF TEST EVAL.

PROGRAM SS

DATE 9-17-76

RUN NO. 18

MICROPHONE NO. 2

OVERALL LEVEL 147

RUN DURATION 10 SEC

TEST ENGINEER SNYDER


TEST TECHNICIAN ROBERSON

REMARKS HELIUM

Plot # 80

INTERNAL

ACOUSTIC DATA SHEET



TEST ITEM LINER

TYPE OF TEST EVAL

PROGRAM SS

DATE 4-17-76

RUN NO. 19

MICROPHONE NO. 3

OVERALL LEVEL 138

RUN DURATION 10 SEC

TEST ENGINEER SNYDER


TEST TECHNICIAN ROBERSON

REMARKS HELIUM

Plot # 81

INTERNAL

ACOUSTIC DATA SHEET



TEST ITEM LINER

TYPE OF TEST EVAL

PROGRAM SS

DATE 9-17-76

RUN NO. 20

MICROPHONE NO. 4

OVERALL LEVEL 134.5

RUN DURATION 10 SEC

TEST ENGINEER SNYDER

TEST TECHNICIAN ROBERTSON

REMARKS HELIUM


Plot # 82

INTERNAL

A84

REPRODUCIBILITY OF THE
ORIGINAL PAGE IS POOR

ACOUSTIC DATA SHEET



TEST ITEM LINER

TYPE OF TEST EVAL

PROGRAM SS

DATE 9-17-70

RUN NO. 21

MICROPHONE NO. 5

OVERALL LEVEL 138

RUN DURATION 10 SEC

TEST ENGINEER SNYDER


TEST TECHNICIAN ROBERSON

REMARKS Helium

Plot # 83

INTERNAL

ACOUSTIC DATA SHEET



TEST ITEM LINER

TYPE OF TEST EVAL

PROGRAM SS

DATE 9-17-76

RUN NO. 22

MICROPHONE NO. 6

OVERALL LEVEL 136

RUN DURATION 10 SEC

TEST ENGINEER SNYDER

TEST TECHNICIAN ROBERSON

REMARKS HELIUM

Plot #84

INTERNAL